

LDRD Annual Report 2013

Y. Chen

November 8, 2013

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

Accomplishment (800 characters):

(1) We developed and fabricated a modified target design integrating the laser wakefield acceleration gas cell design with an angled foil holder for proton beam generation via target normal sheath acceleration (TNSA). (2) The experiment was conducted at the JLF using the Callisto laser. Diagnostics for measuring TNSA proton beam characteristics were set up including RCF stacks, Thomson parabola and imaging plates (3) The self-guiding length in the gas cell for optimized contrast enhancement was estimated to be ~4mm and compared to experiment. Beam emission characteristics were improved using our new design. (4) Preliminary data analysis were performed, detailed analysis and comparison to simulations are underway.

Project Summary Statement (800 characters):

Target normal sheath acceleration (TNSA) by self-guided laser pulses is demonstrated at a range of Al target thickness (2-10 microns), and proton spectra are compared with those accelerated by un-guided laser pulses. For un-guided pulses, the maximum proton energy decreases with the decrease of target thickness, exhibiting the detrimental effect of laser pre-pulse on TNSA. On the other hand, the dependence of proton energy on target thickness was not observed when using self-guided laser pulses, which is possibly due to the suppressed pre-pulse intensity. However the laser pulse appears to lose a significant amount of energy (>~50%) during ~4mm self-guiding in the plasma, and thus the accelerated proton energy is much lower than the case of unguided pulses.

Next Step (one sentence):

We will continue developing this contrast enhancement technology by increasing the laser energy throughput while keeping the low prepulse intensity. This requires better understanding in the relativistic self-guiding process via further experimental and simulation works. This study will have an impact on the understanding of laser prepulse on TNSA.